

DS-UAP300M WIFI EXTENDER IN WALL ACCESS POINT



WIFI



NETWORK



USB



Hardware Specifications	Chipset: MT7628KN; DDR: 8MB; Flash: 2MB
Antenna	2*2dBi Internal Antennas
Wireless Standards	IEEE802.11b/g/n
RF Parameters	Output Power (Max): 80mW(19dBm); Receiving Sensitivity (Max): -91dBm; Working Frequency: 2.412GHz-2.4835GHz
Modulation Mode	DSSS: DBPSK@1Mbps, DQPSK@2Mbps, CCK@5.5/11Mbps; OFDM: BPSK@6/9Mbps, QPSK@12/18Mbps, 16-QAM@24Mbps, 64-QAM@48/54Mbps;
Wireless Rate	300Mbps
Physical Ports	1* 10/100/Mbps WAN RJ45 Port; Support 48V POE; 1* 10/100/Mbps LAN RJ45 Port; 1* USB2.0 Port 0.5A/5V;
Indicator	Wifi Indicator, LED light
Power	Power Supply: 802.3af/802.3at POE Power Supply(0-100m); (If you do not have a POE power supply, you need to purchase a POE power module or use it with a POE power supply)
Power Consumption	<5W
IP Index	IP41
MTBF	>250000H
Installation Way	In Wall Installation
Case	Plastic Case (Imported ABS Material)
Physical Features	Size: 86*86*33mm; Weight: 98g
Working Environment	Working Temperature: 0 C ⁰ -40 ⁰ C; Storage Temperature: -40 C ⁰ -70 C ⁰ ; Operation Humidity: 10%-90%RH Non condensing; Storage Humidity: 5%-90%RH Non condensing